

Front Hub (MTB) Specifications (Standard /Disc Brake/Roller Brake)

Series		XTR	DXR	Deore XT	Deore LX	Deore	Alivio
Model No.		HB-M970	HB-MX70	HB-M770-S	HB-T660	HB-M590	HB-MC12-P
Spoke Holes	24H	-	-	-	-	-	-
	28H	X	-	-	-	-	-
	32H	X	X	X	X	X	X
	36H	X	X	X	X	-	X
	40/48H	-	-	-	-	-	-
	Hole PCD (mm)	40	40	40	38	38	38
O.L.D. (mm)		100	100	100	100	100	100
Flange Diameter (mm)		50.4	50.4	50.4	48.4	48.4	46
Flange Distance		74	74	74	71.6	71.6	71.6
Axle(QR type)	QR Skewer Length	133mm	-	133mm	133mm	133mm	129/133mm
	Axle Length	108mm	-	108mm	108mm(M10)	108mm(M10)	108mm(M9)
	Diameter(mm)	14	14	14	10	10	9
	Material	Aluminum	Aluminum	Aluminum	Steel	Steel	Steel
Axle(Nut type)	Axle Length	-	-	-	-	-	140mm(M9)
	Material	-	-	-	-	-	Steel
Seal		X	X	X	X	X	X
Stainless Steel Ball Bearings		X	X	-	-	-	-
Internal Grease Sleeve		X	X	X	X	-	-
Hub Shell	Material	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum
	Finish	Anodized	Anodized	Anodized	Anodized	Anodized	Anodized
CBN (Cubic Boron Nitride)	Cone Races	X	X	X	X	X	-
	Cup Races	X	X	-	-	-	-
Quick Release Lever	Material	Aluminum	-	Aluminum	Aluminum	Aluminum	Aluminum
	Finish	Anodized	-	Anodized	Anodized	Anodized	Barrel
Radial Lacing		X	X	X	X	X	-
Note			For BMX racing	Silver Version			Black Version Available